

	<b>INSTRUMENT DATA SHEET</b>	<b>DOCUMENT NO. 100-0121</b>
<b>SAGE GENERAL PURPOSE THERMAL MASS FLOW METER</b>	<b>GAS MASS FLOW</b>	<b>SAGE SIG SPECIFICATIONS INTEGRAL STYLE GENERAL PURPOSE IN-LINE MASS FLOW METER</b>

**GENERAL INFORMATION**

<b>STYLE:</b>	Integral In-Line Mass Flow Meter
<b>SENSOR:</b>	Two reference grade platinum RTD clad in 316SS sheath
<b>MATERIAL:</b>	Wetted metal components: 316SS
<b>POWER:</b>	24VDC Standard (12VDC or 115/230VAC optional)
<b>POWER DISSIPATION:</b>	<8 w
<b>ELECTRONICS:</b>	Microprocessor based
<b>ELECTRONICS ENCLOSURE:</b>	Integral mount, weathertight NEMA 4X enclosure
<b>DISPLAY:</b>	Two line, backlit display with keypad (Flow Rate, Totalized Flow, Temperature displayed)
<b>TURNDOWN:</b>	100 to 1
<b>RESOLUTION:</b>	1000 to 1
<b>LOW END SENSITIVITY:</b>	5 SFPM
<b>FIELD CALIBRATION CHECK:</b>	Yes - Digital system allows raw signal validation (milli-watts)
<b>COMMUNICATIONS:</b>	RS232 Communication and Menuing Software (Sage VI_Terminal)
<b>APPROVALS:</b>	No Approvals (only Insertion Style Remote approved [SRG] with 24 VDC Power)
<b>FIELD RECONFIGURABLE:</b>	Optionally available with up to four independent calibrations (Channels A-D)
<b>FLOW ACCURACY:</b>	+/- 0.5% of Full Scale +/- 1% of reading
<b>FLOW REPEATABILITY:</b>	0.2%
<b>RESPONSE TIME:</b>	1 second
<b>GAS TEMPERATURE RANGE:</b>	-40° TO 200°F STD (if higher temperature needed, contact Sage)
<b>GAS PRESSURE:</b>	500 PSIG (if higher pressure needed, contact Sage)
<b>FLOW OUTPUT:</b>	4 to 20 mA for Rate; 24VDC pulse for Totalized value (via Relay contacts)
<b>TEMPERATURE OUTPUT:</b>	4 to 20 mA (Separate output)
<b>AMBIENT TEMPERATURE:</b>	-4° F TO 150°F
<b>FLOW BODY:</b>	316SS Schedule 40 Flow Bodies sized from 1/4" x 6" long to 4" x 12" long. Male NPT ends standard (options available contact Sage)
<b>RELAYS:</b>	Two: Pulsed outputs of Totalized Flow; Alarms (Trip High/Trip Low)
<b>FLOW CONDITIONING:</b>	Flow Conditioners are built in to In-Line Style Flow Bodies from 1/2" to 4"

**Make the Wise Choice. Choose Sage Flow Meters.**

