



INSTRUMENT DATA SHEET

DOCUMENT NO. 100-0329 Rev. 2

**SAGE 200 SERIES
THERMAL MASS FLOW
METER**

GAS MASS FLOW

**SAGE 200 SERIES SPECIFICATIONS
INTEGRAL STYLE
INSERTION MASS FLOW METER**

GENERAL INFORMATION

STYLE:	Integral Insertion Mass Flow Meter
SENSOR:	Two reference grade platinum RTD clad in 316SS sheath or Hastelloy C276
MATERIAL:	Wetted metal components: 316SS or Hastelloy C276
POWER:	24VDC Standard (90-265VAC optional)
POWER DISSIPATION:	<2.5 W
ELECTRONICS:	Microprocessor based (Hybrid-Digital)
ELECTRONICS ENCLOSURE:	Integral mount, NEMA 4 enclosure
DISPLAY:	Flow Rate, Totalizer & Temperature (optional).
TURNDOWN:	100 to 1
RESOLUTION:	1000 to 1
LOW END SENSITIVITY:	5 SFPM
COMMUNICATIONS:	Modbus® compliant RS485 RTU optional
APPROVALS:	Class I, Div 2, Groups B, C, D T4 (24VDC) ANSI/ISA 12.12.01, CSA C22.2; CE (AC Power or 24VDC)
FIELD RECONFIGURABLE:	Sage ADDRESSER or Modbus required
FLOW ACCURACY:	+/- 0.5% of Full Scale +/- 1% of reading
FLOW REPEATABILITY:	0.2%
RESPONSE TIME:	1 second time constant
GAS TEMPERATURE RANGE:	Standard -40° to 200°F (93°C), Optional to 300°F (149°C) and 450°F (232°C)
GAS PRESSURE:	500 PSIG (If higher pressure needed, contact Sage)
FLOW OUTPUT:	4 to 20 mA for Rate
TOTALIZER:	24VDC Pulse for Totalized Value
TEMPERATURE OUTPUT:	Through Modbus® only
AMBIENT TEMPERATURE:	-40° to 150°F (66°C)
PROBE STYLE / LENGTH:	1/2" O.D Probe & Lengths 6" to 36"
RELAYS:	N/A
FLOW CONDITIONING:	Captive Flow Conditioners available upon request with meter purchase
ENCLOSURE DEPTH:	DC: 4.35" ; AC: 5.35"

Make the Wise Choice. Choose Sage Flow Meters.

