

	INSTRUMENT DATA SHEET	DOCUMENT NO. 100-0339 Rev. 2
SAGE PARAMOUNT THERMAL MASS FLOW METER	GAS MASS FLOW	SAGE 401 SPECIFICATIONS INTEGRAL STYLE PARAMOUNT INSERTION MASS FLOW METER

GENERAL INFORMATION

STYLE:	Integral Insertion Mass Flow Meter
SENSOR:	Platinum RTD clad in 316SS sheath
MATERIAL:	Wetted metal components: 316SS
POWER:	24VDC Standard (115/230VAC optional) 2.5 W max power dissipation
SOFTWARE:	SageCom Validation and Reconfiguration Software supplied at no charge
ELECTRONICS:	Microprocessor based (Digital)
ELECTRONICS ENCLOSURE:	Integral mount, dual-sided explosion proof, NEMA 4X enclosure
DISPLAY:	High contrast photo-emissive OLED graphical display (Flow Rate, Total, Temperature, mW)
TURNDOWN:	100 to 1
RESOLUTION:	1000 to 1
LOW END SENSITIVITY:	5 SFPM
FIELD CALIBRATION CHECK:	Yes - Digital system allows raw signal validation (mW)
COMMUNICATIONS:	Modbus® compliant RS485 RTU (opt'l BACnet or HART Communications)
APPROVALS:	CSA C22.2 (24 VDC); UL1604, Class I, Div 2, Groups B, C, D T4 (24VDC); CE (AC Power or 24VDC); ATEX eX nA IIC T4 X; Div 1 (Pending - March 2020)
FIELD RECONFIGURABLE:	SageCom (included)
FLOW ACCURACY:	+/- 0.5% of Full Scale +/- 1% of reading (Enhanced accuracy optionally available with limited turn-down)
FLOW REPEATABILITY:	0.2%
RESPONSE TIME:	1 second time constant
GAS TEMPERATURE RANGE:	Standard -40° to 200°F (93°C), Optional to 300°F (149°C) and 450°F (232°C)
GAS PRESSURE:	500 PSIG (If higher pressure needed, contact Sage)
FLOW OUTPUT:	4 to 20 mA for Rate
TOTALIZER:	24VDC pulse for Totalized value
TEMPERATURE OUTPUT:	Through Modbus® or BACnet
AMBIENT TEMPERATURE:	-40° to 150°F (66°C)
PROBE STYLE/ LENGTH:	½" OD Probe (¾" optional) Lengths 6" to 36" (up to 48" with ¾" Probe)
2ND COMMUNICATION CHANNEL:	Separate mini USB connector and cable
FLOW CONDITIONING:	Captive Flow Conditioners available upon request with meter
ENCLOSURE DEPTH:	8.00"

Make the Wise Choice. Choose Sage Flow Meters.

